

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 1/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

Specifications

TFT-LCDmodule

Model No: QD3579

Customer name:

The project name:

For Customer's Acceptance	
Approved by	Comment

	Signature	Date
Prepared by		
Checked by		
Approved by		

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 2/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

Contents

1	General Description	3
1.1	Features	3
1.2	Application	3
2	Outline Dimension	4
3	Electrical Characteristics	5
3.1	TFT-LCD Module	5
3.2	Back-Light Unit	5
4	Block Diagram	6
5	TFT-LCM Interface Specification	7
6	Description of Interface'Signal	8
6.1	RGB Interface Timing Characteristics	8
6.2	DC Characteristics	8
6.3	AC Characteristics	9
6.4	Reset Characteristics	9
7	Optical Specification	10
8	Environment Absolute Maximum Ratings	13
9	Reliability Test Items	13
10	Inspection Standard	14
11	Package	15
12	Precautions	16
12.1	Handling	16
12.2	Storage	16
12.3	Operation	17
12.4	Touch Panel Mounting Notes	17
12.5	Others	18
13	Records of Version	19

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 3/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

1 General Description

QD3579 is a transmissive type a-Si TFT-LCD (amorphous silicon thin film transistor liquid crystal display) module, which is composed of a TFT-LCD panel, a driver circuit a backlight unit, The panel size is3.5inch and thresolution is 320x480. High image quality a-Si TFT LCD module. Partial-screen display function is available. Sleep and Stand-by modes are available for power saving.

1.1 Features

No	Item	Specification	Remark
1	Display Mode	Normally Black	
2	Screen Size	3.5inch (diagonal)	
3	Resolution	320XRGBX480	
4	Color Number	262K	
5	Color Arrangement	RGB-stripe	
6	Driver IC	ST7796U	
7	Back Light	White LED*6	
8	Viewing Direction	12O'CLOCK	
9	Interface	MCU_SPI_RGB 兼容	
10	Surface Treatment	UV Cut	

1.2 Application

- ◆ Mobile phone.
- ◆ Portable multimedia device.

2 Outline Dimension

The mechanical detail is shown in Fig. 1 and summarized in Table 1 below.

Parameter	Specifications	Unit
Outline dimensions	55.5 (W) x84.96(H) x3.7±0.1(D) (LCM,no include FPC)	mm
Active area	48.96(W) x73.44(H)	mm
Resolution	320(H)RGBx 480(V) dots	-
Dot size	0.153(H) ×0.153	mm
Module brightness	260	cd/m²

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 5/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

Figure 1: Module specification of the module

3 Electrical Characteristics

3.1 TFT-LCD Module

Ta=25℃

Item	Symbo	Value			Unit	Notes
		Min	Typ	Max		
Supply Voltage for logic	Vcc	2.5	2.8	3.3	V	
	Vci	2.5	2.8	3.3		
TFT Gate ON Voltage	VGH *	11.5		19	V	
TFT Gate OFF Voltage	VGL	-15.5		-7	V	
Operating temperature	Top	-20		+70	℃	
Storage temperature	Tst	-30		+80	℃	

3.2 Back-Light Unit

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
Current	IF	--	120	140	mA	IF=120mA VF=3.0V
Forward voltage	VF	3.0	3.2	3.3	V	
Chroma	X	0.240		0.28		
	Y	0.250		0.29		
Brightness	L	4500			Cd/m2	
Uniformity	UBL	80			%	

- 6 LED
- The luminous intensity of LED is strongly dependent on the driving current.
- It is recommended the input of backlight to be constant current rather than constant voltage.

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 7/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

Pin No.	Symbol	Functional	Notes
1	YU	Y+	
2	XL	X-	
3	YD	X-	
4	XR	X+	
5	VCC	Power supply input for LCM:2.8V	
6	IOVCC	Power supply input for LCM: 1.8V	
7	TE	Serve as a TE (Tearing Effect) output signal	
8	CS	Chip select input pin.	
9	RS/A0	The SPI interface (DCX): The signal for command or	
10	WR/SCL	A write strobe signal can be input via this pin and initiallizes a write Serial clock input for SPI interface	
11	RD	A read strobe signal can be input via this pin and initiallizes a read	
12	SDI	Serial data input/output bidirectional pin for SPI Interface	
13	SDO	Serial data output pin used for the SPI Interface	
14	GND	Power Ground	
15~32	DB0~DB17	Data interface	
33	GND	Power Ground	
34	DEN	Data enable signal	
35	PCLK	Dot clock signal for RGB interface operation	
36	HSYNC	Horizontal sync	
37	VSYNC	Vertical sync	
38	RESET	Reset signal input Pin	
39~41	IM2-IM0	The System interface mode select	
42	LEDA	Power supply for backlight anode input terminal.	
43~48	LED-K	Power supply for backlight cathode input terminal.	

5 TFT-LCM Interface Specification

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 8/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

6 Description of Interface'Signal

6.1 RGB Interface Timing Charateristics





Figure 28 Timing Chart of Signals in RGB Interface DE Mode

6.2 DC Characteristics

Parameter	Symbol	Condition	Specification			Unit	Related Pins
			MIN.	TYP.	MAX.		
Power & Operation Voltage							
System Voltage	VDD / VDDA	Operating voltage	2.5	2.75	3.3	V	
Interface Operation Voltage	VDDI	I/O Supply Voltage	1.65	1.8	3.3	V	
Gate Driver High Voltage	VGH		12.54		15.46	V	
Gate Driver Low Voltage	VGL		-12.5		-7.15	V	
Gate Driver Supply Voltage		VGH-VGL			27.96	V	
Input / Output							
Logic-High Input Voltage	VIH		0.7VDDI		VDDI	V	Note 1
Logic-Low Input Voltage	VIL		VSS		0.3VDDI	V	Note 1
Differential Input High Threshold Voltage	VIT+			0	50	mV	MIPI_CLK, MIPI_DATA
Differential Input Low Threshold Voltage	VIT-		-50	0		mV	
Single-ended Receiver Input Operation Voltage Range	VIR		0.5		1.2	V	
Logic-High Output Voltage	VOH	IOH = -1.0mA	0.8VDDI		VDDI	V	Note 1
Logic-Low Output Voltage	VOL	IOL = +1.0mA	VSS		0.2VDDI	V	Note 1
Logic-High Input Current	IIH	VIN = VDDI			1	uA	Note 1
Logic-Low Input Current	IIL	VIN = VSS	-1			uA	Note 1
Input Leakage Current	ILI	IOH = -1.0mA	-0.1		+0.1	uA	Note 1
VCOM Voltage							
VCOM Voltage	VCOM			VSS		V	
Source Driver							
Gamma Reference Voltage(Positive)	VAP		4.45		6.4	V	
Gamma Reference Voltage(Negative)	VAN		-4.6		-2.65		
Source Output Settling Time	Tr	Below with 99% precision			20	us	Note 2

6.3 AC Characteristics



VDDI=1.8V,VDDA=2.8V, AGND=DGND=0V, Ta=25℃

Signal	Symbol	Parameter	MIN	MAX	Unit	Description
HSYNC, VSYNC	T_{SYNCS}	VSYNC, HSYNC Setup Time	15	-	ns	
ENABLE	T_{ENS}	Enable Setup Time	15	-	ns	
	T_{ENH}	Enable Hold Time	15	-	ns	
DOTCLK	PWDH	DOTCLK High-level Pulse Width	30	-	ns	
	PWDL	DOTCLK Low-level Pulse Width	30	-	ns	
	T_{CYCD}	DOTCLK Cycle Time	66	-	ns	
	Trghr, Trghf	DOTCLK Rise/Fall time	-	15	ns	
DB	T_{PDS}	PD Data Setup Time	15	-	ns	
	T_{PDH}	PD Data Hold Time	15	-	ns	

6.4 Reset Timing

7.5.6 Reset Timing:




Figure 10 Reset Timing

VDDI=1.8,VDD=2.8, AGND=DGND=0V, T_a=25 °C

Related Pins	Symbol	Parameter	MIN	MAX	Unit
RESX	TRW	Reset pulse duration	10	-	us
	TRT	Reset cancel	-	5 (Note 1, 5)	ms
				120(Note 1, 6, 7)	ms


Table 10 Reset Timing

Notes:

1. The reset cancel includes also required time for loading ID bytes, VCOM setting and other settings from NVM (or similar device) to registers. This loading is done every time when there is HW reset cancel time (TRT) within 5 ms after a rising edge of RESX.
2. Spike due to an electrostatic discharge on RESX line does not cause irregular system reset according to the table below:

RESX Pulse	Action
Shorter than 5us	Reset Rejected
Longer than 9us	Reset
Between 5us and 9us	Reset starts

3. During the Resetting period, the display will be blanked (The display is entering blanking sequence, which maximum time is 120 ms, when Reset Starts in Sleep Out =mode. The display remains the blank state in Sleep In =mode.) and then return to Default condition for Hardware Reset.
4. Spike Rejection also applies during a valid reset pulse as shown below;



5. When Reset applied during Sleep In Mode.
6. When Reset applied during Sleep Out Mode.
7. It is necessary to wait 5msec after releasing RESX before sending commands. Also Sleep Out command cannot be sent for 120msec.


深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 12/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

7. Optical Specification

Item	Symbol	Condition	Specification			Unit	Remark
			Min.	Typ.	Max.		
Response time (By Quick)	Tr+Tf	$\theta=0^{\circ}$	-	20	40	ms	Note 5
Contrast ratio	CR	$\theta=0^{\circ}$	-	500	-		Note 2,6
Viewing angle	Top	$CR \geq 10$	-	60	-	deg.	Note 2,6,7
	Bottom	$CR \geq 10$	-	60	-		
	Left	$CR \geq 10$	-	70	-		
	Right	$CR \geq 10$	-	70	-		
Color chromaticity (CF only with ITO, light source is C light, CIE 1931)	Wx	$\theta=0^{\circ}$	0.292	0.307	0.322		Note 3
	Wy		0.312	0.327	0.342		
	Rx		0.609	0.624	0.639		
	Ry		0.316	0.331	0.346		
	Gx		0.281	0.296	0.311		
	Gy		0.562	0.577	0.592		
	Bx		0.128	0.143	0.158		
	By		0.094	0.109	0.124		
NTSC			57%	60%	-		Note 3
Cross talk	Ct		-	-	2%		Note 9
Transmittance	Trans		-	5.50%	-		Note 4

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 13/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	


Note 1: The brightness test equipment setup
I_B=60mA, Field=2° (As measuring “black” image, field=2° is the best testing condition.)



Note 2: Definition of contrast ratio (C.R)

$$C.R = \frac{\text{Brightness When LCD is at "White" State}}{\text{Brightness When LCD is at "Black" State}}$$

Note 3: Definition of response
time




深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 15/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

8 Environment Absolute Maximum Ratings

Item	Symbol	Min	Max	Unit	Remark
Operation temperature range	Top	-20	70	℃	Ambient
Storage temperature range	Tst	-30	80	℃	Ambient

- Corrosive gas environment is not acceptable.
- TFT-LCD color will change slightly depending on environment temperature. This phenomenon is reversible. Current reduction rate of LED backlight is according to the graph indicated below:



深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 16/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

9 Reliability Test Items


Test Item	Test Condition
High Temperature Operation	70℃ for 24 hours
Low Temperature Operation	-20℃ for 24 hours
High Temperature Storage	70℃ for 24 hours
Low Temperature Storage	-40℃ for 24 hours
High Temperature Operation Humidity Operation	50℃ , 95%RH for 48 hours
Thermal Shock	-30°storage one hour, rise to 70° within 15s, high temperature one hour, drop to 30° within 15s, circulate ten repeatedly
Vibration Test (No Operation)	Frequency: 10~55Hz Amplitude: 1.0mm Sweep Time: 11min Test Period: 6 Cycles for each direction of X, Y, Z
Static electricity test	Touch 6KV, air touch 10KV

10 Inspection Standard

This standard apply to TFT module specification.

1. Inspection condition:

Under daylight lamp 20~40W, product distance inspector'eye 30cm.incline degree 30° .









2. Inspection standard

NO.	Item	Inspection standard	Rate															
2.1	Dot	<p>Case of Dot defect is below</p> <p>① Bright Dot (whit spot) : "0"</p> <p>② Dark Dot (black spot) : "0" (In case of Dark Dot on Main TFT LCD)</p> <p>- NG if there's full Dot defect.</p> <p>- Damaged less than the size of sub-pixel is not counted as defect</p> <p>- Dots darker than the size of sub-pixel are not defined as bright dot defect</p> <table><tr><th>area size (mm)</th><th>Acceptable number</th></tr><tr><td>$\Phi \leq 0.10$</td><td>ignore</td></tr><tr><td>$0.10 < \Phi \leq 0.15$</td><td>3</td></tr><tr><td>$0.15 < \Phi \leq 0.20$</td><td>2</td></tr><tr><td>$0.25 < \Phi \leq 0.25$</td><td>1</td></tr><tr><td>$0.25 < \Phi$</td><td>0</td></tr></table>	area size (mm)	Acceptable number	$\Phi \leq 0.10$	ignore	$0.10 < \Phi \leq 0.15$	3	$0.15 < \Phi \leq 0.20$	2	$0.25 < \Phi \leq 0.25$	1	$0.25 < \Phi$	0	minor			
area size (mm)	Acceptable number																	
$\Phi \leq 0.10$	ignore																	
$0.10 < \Phi \leq 0.15$	3																	
$0.15 < \Phi \leq 0.20$	2																	
$0.25 < \Phi \leq 0.25$	1																	
$0.25 < \Phi$	0																	
2.2	line	<table><tr><th colspan="2">Size (mm)</th><th>Acceptable number</th></tr><tr><td>ignore</td><td>$W \leq 0.03$</td><td>ignore</td></tr><tr><td>$L \leq 4.0$</td><td>$0.03 < W \leq 0.04$</td><td>2</td></tr><tr><td>$L \leq 4.0$</td><td>$0.04 < W \leq 0.05$</td><td>1</td></tr><tr><td></td><td>$0.05 < W$</td><td>Treat with dot non-conformance</td></tr></table>	Size (mm)		Acceptable number	ignore	$W \leq 0.03$	ignore	$L \leq 4.0$	$0.03 < W \leq 0.04$	2	$L \leq 4.0$	$0.04 < W \leq 0.05$	1		$0.05 < W$	Treat with dot non-conformance	
Size (mm)		Acceptable number																
ignore	$W \leq 0.03$	ignore																
$L \leq 4.0$	$0.03 < W \leq 0.04$	2																
$L \leq 4.0$	$0.04 < W \leq 0.05$	1																
	$0.05 < W$	Treat with dot non-conformance																

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 18/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

11 Package

1 	4 
10 pcs per tray + 1 cover (EPE)	Packing bag
2 	5 
15 trays + 1 dummy tray = 150 ps	Putting bag into carton Protected by 2 pieces of cushion EPE sheet
3 	6 
Putting trays into anti-electrostatic bag	Packing carton with sealing tape

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 19/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

	Carton outline size: 400×295×145 (mm)
--	---------------------------------------

12 Precautions

Please pay attentions to the followings as using the LCD module.

12.1 Handling

- (a) Do not apply strong mechanical stress like drop, shock or any force to LCD module. It may cause improper operation, even damage.
- (b) Because the polarizer is very fragile and easy to be damaged, do not hit, press or rub the display surface with hard materials.
- (c) Do not put heavy or hard material on the display surface, and do not stack LCD modules.
- (d) If the display surface is dirty, please wipe the surface softly with cotton swab or clean cloth.
- (e) Avoid using Ketone type materials (e.g. Acetone), Toluene, Ethyl acid or Methyl chloride to clean the display surface. It might damage the touch panel surface permanently. The recommended solvents are water and Isopropyl alcohol.
- (f) Wipe off water droplets or oil immediately.
- (g) Protect the LCD module from ESD. It will damage the LSI and the electronic circuit.
- (h) Do not touch the output pins directly with bare hands.
- (i) Do not disassemble the LCD module.
- (j) Do not lift the FPC of Touch Panel.

12.2 Storage

- (a) Do not leave the LCD modules in high temperature, especially in high humidity for a long time.
- (b) Do not expose the LCD modules to sunlight directly.
- (c) The liquid crystal is deteriorated by ultraviolet. Do not leave it in strong

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 20/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

ultraviolet ray for a long time.

- (d) Avoid condensation of water. It may cause improper operation.
- (e) Please stack only up to the number stated on carton box for storage and transportation. Excessive weight will cause deformation and damage of carton box.

12.3Operation


- (a) When mounting or dismounting the LCD modules, turn the power off.
- (b) Protect the LCD modules from electric shock.
- (c) The Driver IC control algorithms stated above should always obeyed to avoid damaging the LSI and electronic circuit.
- (d) Be careful to avoid mixing up the polarity of power supply for backlight.
- (e) Absolute maximum rating specified above has to be always kept in any case. Exceeding it may cause non-recoverable damage of electronic components or, nevertheless, burning.
- (f) When a static image is displayed for a long time, remnant image is likely to occur.
- (g) Be sure to avoid bending the FPC to an acute shape, it might break FPC.
- (h) Most of the touch screens have air vent to equalize the inside air pressure to the outside one. The air vent must be open and liquid contact must be avoided as the liquid may be absorbed if the liquid is accumulated near the air vent.
- (i) For the fragility of ITO film, it should avoid to use too tapering pen as the input material.

12.4Touch Panel Mounting Notes

- (a) If a cushion is used between bezel/housing and film must be choose as free as enough to absorb the expansion and contraction to avoid the distortion of film.
- (b) The cushion must be placed out of the Viewing Area.
- (c) Bezel/Housing edge must be posited between Key Area and Viewing Area. The edge enters the Key Area may cause unexpected input if the gap is too narrow or foreign particles like dusts exist between Bezel/Housing and ITO film.

深圳市科易互动机器人有限公司	Doc.No.:	
	REV : A	PAGE : 21/22
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE : 2024.08.15	

(d) Mounting example:



The corner part has conductivity. Do not touch any metal part after mounting.

12.5Others

- a) If the liquid crystal leaks from the panel, it should be kept away from the eyes or mouth.
- b) For the fragility of polarizer, it is recommended to attach a transparent protective plate over the display surface.
- c) It is recommended to peel off the protection film on the polarizer slowly so that the electrostatic charge can be minimized.

